



CCS Same Day Sealer

DESCRIPTION

CCS Same Day Sealer is a ready to use, solvent based, acrylic sealer, designed for application to freshly laid concrete.

It is designed to assist with curing and to provide a protective primer coat prior to later sealing with a more durable CCS Sealer.

RECOMMENDED USES

CCS Same Day Sealer is a curing/priming coat for application on:-

- Full Depth Coloured Concrete
- Exposed Concrete
- Stencilled Concrete.

These surfaces should then be sealed after a minimum of three days with one coat of *CCS Hardseal* or *CCS Hardseal Enduro*.

PACKAGING

CCS Same Day Sealer is available in 20 litre and 200 litre drums.

FEATURES

Application of *CCS Same Day Sealer* to fresh concrete surfaces will assist in enhancing curing, inhibiting the incidence of efflorescence, while providing immediate protection from marking by other tradesmen.

COVERAGE

For application where one coat is applied, coverage is typically up to 5m² per litre. Porosity of surface will impact on this figure.

APPLICATION GUIDELINES

(Please refer to the product label on the drum)

Apply *CCS Same Day Sealer* to freshly laid concrete once concrete has cured enough to be walked on by the contractor (*CCS Same Day Sealer* should be applied the same day as concrete was placed).

This product is best applied using a low-pressure sprayer.

CURING TIME

Curing time depends on the temperature. The sealer is usually touch dry in 20 minutes at 25 ° Celsius.

It is important to allow a minimum of three days before applying the topcoat of *CCS Hardseal* or *CCS Hibuild Enduro*.

CLEAN UP

Wash all equipment thoroughly in *CCS Solvent* and allow to dry.

HEALTH AND SAFETY

- *CCS Same Day Sealer* is flammable. Avoid contact with heat and naked flame.
- Avoid contact with the skin and eyes
- Use gloves, mask and goggles during application
- Provide adequate ventilation when using in confined spaces
- If swallowed, seek medical attention immediately.

For further information consult the **Material Safety Data Sheet** and read the product label carefully before use. **Material Safety Data Sheets** are available by phoning **1800 077 744**.

Please Note:- The information given in this data sheet is based on our current knowledge of the product when properly stored, handled and applied. We cannot guarantee that the product will be suitable, effective or safe when used for any purpose other than its stated uses.

To the extent that it is lawful, we exclude warranties implied by law and limit our liability to the cost of replacing the product. We accept no responsibility for loss or injury caused by improper use, incompetent preparation, inexperienced or negligent application, or ordinary wear and tear.

Service or advice given by our staff should not amount to responsibility for the project - since the owner, or their contractor (and not River Sands), is responsible for procedures relating to the application of the product.



Concrete Colour Systems
A Division of River Sands Pty Ltd
683 Beenleigh Redland Bay Rd,
Carbrook Qld 4130
Ph: 07 3287 6444 Fax: 07 3287 6445
Sydney: (02) 9756 1711
Melb: (03) 9311 9225
Perth: 0423 023 164
Toll Free Helpline: 1800 077 744
www.concretocoloursystems.com.au