

ACRYLOC® ROOF CLEAN

Data Sheet: TECH15005

PRODUCT TYPE

Preparation Products

PACKAGING

200L Heavy Duty Plastic Drum

NOMINAL WEIGHT

244kg

PRODUCT & STOCK CODES

Roof Clean

15005

DESCRIPTION

Acryloc *Roof Clean* is a high grade product designed specifically for releasing moss, lichen, and minor deposits of grease and oil from various substrates to make subsequent pressure cleaning faster and more effective.



MAIN USES

Acryloc *Roof Clean* is recommended for cleaning roof tiles as part of a roof restoration and can be used on cement, fibro cement & terracotta roofing tiles, walls, floors, driveways, paths and ceramic tiles where fungal growth, oil or grease has to be removed. Acryloc *Roof Clean* is supplied as a concentrate and must be diluted before use.

FEATURES & BENEFITS

- Easy to apply
- Water based
- Easy clean up

SUITABLE SUBSTRATES

- Cement Render
- Brickwork
- Ceramic tiles
- Roofing tiles
- Driveways & paths
- Concrete blocks
- Clay brick

APPLICATION

WARNINGS

- Acryloc *Roof Clean* is an alkaline, corrosive liquid, may produce severe burns & skin irritation.
- Diluted cleaner must be stored in plastic containers.
- Acryloc *Roof Clean* may attack some surfaces such as aluminium. Test on a small area first
- Areas not to be cleaned should be masked and protected
- **Rainwater tanks must be disconnected from the guttering system** before commencing work and must remain disconnected until after application of all subsequent coatings. It is essential that all residues are washed from the roof and from the guttering.

Dilution– always add Acryloc *Roof Clean* to water, do NOT add water to the *Roof Clean*

Acryloc *Roof Clean* must be diluted before use (hot water should not be used)

- Light to medium duty cleaning (mud, light soiling, road grime, normal roof cleaning)
 - Add 25mls of Acryloc *Roof Clean* to 1Lt of clean water before use
- Heavy duty cleaning (moss, lichen, oils, grease)
 - Add 100ml of Acryloc *Roof Clean* to 1Lt of clean water before use

Method

- Mix thoroughly with a broad, flat stirrer, using an upward lifting action, or power mixer
- Acryloc *Roof Clean* can be applied using a roller, brush, pad, HVLP spray equipment or airless spray equipment. If applying on roofs, application with a garden type weed sprayer is recommended
- If using airless spray equipment, a 15 thou tip and white gun filter is recommended
- **Indoors and Shaded Areas**
 - Apply Acryloc *Roof Clean* liberally to the surface, agitate with a broom or similar and allow to soak for 1-2 hours. Remove by high pressure cleaning followed by hosing with clean water.
- **Roof Areas**
 - Apply Acryloc *Roof Clean* liberally, leave for 1-2 hours, then pressure clean
 - For heavy moss growth, apply Acryloc *Roof Clean* late afternoon or evening and allow to 'soak' overnight before pressure cleaning
- Acryloc *Roof Clean* must be completely removed, preferably by pressure cleaning.

Important Notes

- Avoid application in full sun, on hot surfaces or in hot windy conditions
- Avoid allowing the material to dry out during the soaking period

Clean-Up

Clean up with water

OTHER CONSIDERATIONS**Shelf-Life – Unopened Containers**

Maximum two (2) years from date of manufacture when stored correctly

Transport & Storage

Drums should not be stacked during transportation and must be transported upright

Store in a cool place, upright, out of direct sunlight and above 4°C

For further information refer to **MSDS** for Acryloc *Roof Clean*

TECHNICAL DATA

APPEARANCE	Watery yellow liquid
ODOUR	Low
APPLICATION METHODS	Roller, brush, spray
SPECIFIC GRAVITY (NOMINAL)	~1.04
VOLUME SOLIDS (APPROX)	n/a
WEIGHT SOLIDS (APPROX)	n/a
THEORETICAL COVERAGE	10-15m ² /L per coat at normal dilution
NO. OF COATS	As required, typically 1 coat
SOLVENT FOR CLEANING	Water
FLAMMABILITY	Non-flammable

SAFETY & HANDLING

Refer to **MSDS** for **Acryloc Roof Clean** before use. For further information on Material Safety Data Sheets, call the Acryloc **Tech – Info line** on **1300 661 745** or visit **www.acryloc.com.au**

When working with **Acryloc Roof Clean** observe the following precautions as a minimum:

- Avoid inhalation of the vapour, prolonged skin contact and particularly eye contact
- Wear protective clothing to minimize skin contact and wear goggles where splatter is likely
- Where spills occur, soak up liquid spillage with sand/sawdust and dispose of in a sensible manner. Do not permit run-off to sewer, storm water or open bodies of water



FIRST AID MEASURES

Refer to **MSDS** for **Acryloc Roof Clean** before use. For further information on Material Safety Data Sheets, call the Acryloc **Tech – Info line** on **1300 661 745** or visit **www.acryloc.com.au**

Ingestion

If swallowed, wash out mouth with water. Do **NOT** induce vomiting. Drink at least two (2) glasses of water. Seek medical attention.

Eye

Wash with copious amount of water for 15 minutes holding eyelid(s) open. Take care not to rinse contaminated water into non-affected eye. Seek medical attention.

Advice to Doctor

Treat symptomatically

MANUFACTURED BY:

Bizfine Pty Ltd
T/A Acryloc Building Products
174 Cavan Rd
DRY CREEK SA 5094
AUSTRALIA
P: +61 8 8368 0222
F: +61 8 8349 4260
E: sales@acryloc.com.au
W: www.acryloc.com.au

ORDERS:

F: +61 8 8349 4260
E: store@acryloc.com.au

FOR TECHNICAL ADVICE CALL 1300 661 745

Page 4 of 4

The information provided herein is considered correct at the time of publication. It is the responsibility of those using this information to check that it is current prior to specifying or using any of the products or coating systems. Any advice, recommendation or information provided by any of the officers of Acryloc Building Products in relation to goods manufactured by it for their use and application is given in good faith and is believed by Acryloc Building Products to be appropriate and reliable. However, this advice, recommendation and information is provided without liability or responsibility without excluding or limiting responsibility under relevant Government acts. Acryloc and other marks followed by the symbol ® or ™ are trademarks.

PROUDLY AUSTRALIAN OWNED AND OPERATED