

## ACRYLOC® MOULD RID

Data Sheet: TECH15015

### PRODUCT TYPE

Preparation Products

### PACKAGING

20L Heavy Duty Plastic Pail

### NOMINAL WEIGHT

21.5kg

### PRODUCT & STOCK CODES

Mould Rid Concentrate 15015

Mould Rid Ready To Use 15020

### DESCRIPTION

Acryloc *Mould Rid* is a broad spectrum water based biocide containing proprietary additives which inhibits the growth of moss and lichen on surfaces to which it is applied.

Acryloc *Mould Rid* is available as a concentrate and in a ready to use form. For ease of identification, the concentrate packaging has an orange coloured label.

### MAIN USES

Acryloc *Mould Rid* may be applied to clean cement and unglazed terracotta roofs, and to a range of other substrates, to inhibit the subsequent growth of moss and lichen. Acryloc *Mould Rid* is applied prior to priming and subsequent coatings.

### FEATURES & BENEFITS

- Easy to apply
- Water based
- Easy clean up

### SUITABLE SUBSTRATES

- Pre-cleaned unglazed terracotta tiles
- Pre-cleaned cement tiles
- Cement Render
- AAC (Autoclaved Aerated Concrete)
- Fibre Cement Sheeting (Fibro/Blue board)
- Brickwork
- Concrete blocks
- Clay brick
- Tilt panel walls
- Zinalume®
- Colorbond®
- Galvanised Iron

### WARNING

- **For use on roofs, Rainwater tanks must be disconnected from the guttering system** before application of Acryloc *Mould Rid* and must remain disconnected until after application of all subsequent coatings. It is essential that all residues are washed from the guttering.

### SUBSTRATE PREPARATION

- Areas not to be coated should be masked and protected
- All surfaces to be coated must be clean, sound, free from contaminants including; oil, mould release, dust, dirt, silicone, mud, grease, salt, efflorescence, animal droppings and any loose or flaking material

**APPLICATION****Acryloc Mould Rid Ready To Use**

- *Mould Rid ready to use* can be applied straight from the pail

**Acryloc Mould Rid Concentrate**

- *Acryloc Mould Rid Concentrate* (orange label) must be diluted with before use
- For normal use - Add (1) part *Acryloc Mould Rid Concentrate* to twenty (20) parts of clean water (1:20)
- For severe growth – Add one (1) part *Acryloc Mould Rid Concentrate* to ten (10) parts of clean water (1:10)

**Method**

- Mix thoroughly with a broad, flat stirrer
- Application should be carried out on a day with temperatures above 10°C and below 32°C, and with rainfall not expected for minimum 8 hours to allow time for drying and to apply subsequent coatings. Re application will be necessary if rainfall occurs before *Acryloc Mould Rid* is overcoated
- *Acryloc Mould Rid* can be applied using a roller, brush, pad, HVLP spray equipment or airless spray equipment
- If applying on roofs, application with a garden type weed sprayer is recommended
- Apply enough *Acryloc Mould Rid* to adequately “wet” the surface
- If using airless spray equipment, a 15 thou tip and white gun filter is recommended
- When applied as part of a roof restoration, *Acryloc Mould Rid* must be over coated using the appropriate components selected from the CRC™ system

**Important Notes**

- Avoid application in full sun, on hot surfaces or in hot windy conditions

**Clean-Up**

Clean up with water

**OTHER CONSIDERATIONS****Shelf-Life – Unopened Containers**

Maximum two (2) years from date of manufacture when stored correctly

**Transport & Storage**

Pails should not be stacked more than three (3) high during transportation and must be transported upright

Store in a cool place, upright, out of direct sunlight and above 4°C

For further information refer to **MSDS** for *Acryloc Mould Rid*

**TECHNICAL DATA**

APPEARANCE	Watery bluish liquid		
ODOUR	Low		
APPLICATION METHODS	Roller, brush, spray		
SPECIFIC GRAVITY (NOMINAL)	~ 1.0		
THEORETICAL COVERAGE	10-15m <sup>2</sup> /L per coat when diluted		
WET FILM THICKNESS (RECOMM)	N/A		
DRY FILM THICKNESS (MIN)	N/A		
DRY TIME (25°C & 50% RH) (APPROX)	Tack Free	Overcoat	Fully Dried
	N/A	When dry	N/A
NO. OF COATS	Typically 1 coat		
SOLVENT FOR CLEANING	Water		
FLAMMABILITY	Non-flammable		

---

**SAFETY & HANDLING**

Refer to **MSDS** for **Acryloc Mould Rid** before use. For further information on Material Safety Data Sheets, call the Acryloc Tech – Info line on **1300 661 745** or visit **www.acryloc.com.au**

When working with **Acryloc Mould Rid** observe the following precautions for as a minimum:

- Avoid inhalation of the vapour, prolonged skin contact and particularly eye contact
  - Wear protective clothing to minimize skin contact and wear goggles where splatter is likely
  - Where spills occur, soak up liquid spillage with sand/sawdust and dispose of in a sensible manner. Do not permit run-off to sewer, storm water or open bodies of water
- 

**FIRST AID MEASURES**

Refer to **MSDS** for **Acryloc Mould Rid** before use. For further information on Material Safety Data Sheets, call the Acryloc Tech – Info line on **1300 661 745** or visit **www.acryloc.com.au**

**Ingestion**

If swallowed, wash out mouth with water. Do **NOT** induce vomiting. Drink at least two (2) glasses of water. Seek medical attention.

**Eye**

Wash with copious amount of water for 15 minutes holding eyelid(s) open. Take care not to rinse contaminated water into non-affected eye. Seek medical attention.

**Advice to Doctor**

Treat symptomatically

---

**MANUFACTURED BY:**

Bizfine Pty Ltd  
T/A Acryloc Building Products  
174 Cavan Rd  
DRY CREEK SA 5094  
AUSTRALIA  
P: +61 8 8368 0222  
F: +61 8 8349 4260  
E: sales@acryloc.com.au  
W: www.acryloc.com.au

**ORDERS:**

F: +61 8 8349 4260  
E: store@acryloc.com.au

