

CCS Sealer Grip

DESCRIPTION

CCS Sealer Grip is a specially processed powder, which is designed to be used in conjunction with CCS Hardseal, Hibuild Enduro, and their range of urethane and Epoxy sealers.

It combines with the sealer to form a textured finish which provides greater traction. In contrast to natural aggregates, sealer grip will not settle out when mixed with the sealer. This enables the applicator to seal and treat concrete and masonry surfaces.

RECOMMENDED USES

Use CCS Sealer Grip to increase skid resistance on relatively flat concrete surfaces.

Where the slope of the concrete exceeds a 30-degree angle, we recommend that either a broom finish be used on the concrete, or if this is not possible, an alternative coating with glass bead be applied.

Note: Glass Bead can be used with CCS Armourthane.

PACKAGING

CCS Sealer Grip is available in 280 gram bags.

APPLICATION GUIDELINES

1. The normal rate of application is 14-20 grams per litre (280 gms per 20 litre drum), however more or less can be added depending on the texture that is required.
2. Coat a small area, as a trial to ensure results are adequate.
3. Pour the required quantity of sealer grip powder slowly into the sealer whilst stirring with the other hand.
4. Continue stirring until thoroughly blended.

5. Ensure that the sealer grip is mixed into the selected sealer on the **second coat of application only (Note:- Sealer Grip should not be added to the first coat of sealer as this will affect adhesion of the sealer to the substrate).**

For further information consult the **Material Safety Data Sheet** and read the product label carefully before use. **Material Safety Data Sheets** are available by phoning **1800 077 744**.

***Please Note:-** The information given in this data sheet is based on our current knowledge of the product when properly stored, handled and applied. We cannot guarantee that the product will be suitable, effective or safe when used for any purpose other than its stated uses.*

To the extent that it is lawful, we exclude warranties implied by law and limit our liability to the cost of replacing the product. We accept no responsibility for loss or injury caused by improper use, incompetent preparation, inexperienced or negligent application, or ordinary wear and tear.

Service or advice given by our staff should not amount to responsibility for the project - since the owner, or their contractor (and not River Sands), is responsible for procedures relating to the application of the product.