

## DESCRIPTION

CCS Sheen is a **low VOC (Green Star IEQ-13 compliant)**, water based sealer/polish that adds lustre and shine to unsealed concrete, natural stone, polished concrete and vinyl floors. It is also recommended as the protective polish over the entire range of CCS Platinum Polish Coatings.

CCS Sheen is formulated from selected waxes and resins to produce a protective barrier which extends the life of either clear or coloured base coatings. It is particularly suited to supermarket and terrazzo floors.

CCS Sheen assists with cleaning and maintenance regimes.

## RECOMMENDED USES

- Suitable for internal unsealed concrete, polished concrete, natural stone, terrazzo and vinyl floors in high traffic areas.
- Also suitable as a protective barrier over other base coatings.

## PACKAGING

CCS Sheen is available in a 20 litre container.

## PREPARATION

1. Before applying CCS Sheen, allow all new CCS floor coatings to cure for a minimum of 24 hours.
2. Ensure the surface is clean and free from dust or particles which could scratch the base coating during application.

## APPLICATION METHOD

### Over Newly Applied CCS Armourthane WB or Ultra Glaze Floor Coatings:

1. Apply CCS Sheen using a clean bucket with a cotton mop, lambswool applicator or flat microfibre mop.

### Over New Base Coating

1. Apply 4-5 thin coats of CCS Sheen using a clean bucket with a cotton mop or lambswool applicator. All coats must be applied in the opposite direction to the previous coat to ensure even application.
2. Allow each coat to dry for at least one hour before attempting recoating, buffing and burnishing.

### Over Previously Sealed and Polished Floors:

1. Remove all old sealer coatings using CCS WB Stripper, hot water and auto scrubbing machine with a black nylon pad.
2. Apply 4-5 thin coats of CCS Sheen using a clean bucket with a cotton mop, lambswool applicator or flat microfibre mop. All coats must be applied in the opposite direction to the previous coats to ensure even application.
3. Allow each coat to dry for at least one hour before attempting re-coating, buffing and burnishing.

## MAINTENANCE

1. Dust mop the surface regularly to remove dirt and debris.
2. To remove grime and dirt by applying use CCS Neutral Cleaner GP diluted at the rate of 5-20mls per 10 litres of hot water.
  1. If cleaning is carried out by an auto scrubbing machine use CCS Neutral Cleaner AS (see data sheet for dilution rates and application guidelines).
2. When the gloss requires enhancing, spray and buff the surface with CCS Buff GP or CCS Buff AS when using an auto scrubbing machine. (See data sheet for dilution rates and application guidelines).

## CLEAN UP

Clean tools and equipment with fresh clean water.

## STORAGE

Store away from other chemicals and food. Do not mix with other chemicals.

For further information consult the **Material Safety Data Sheet** and read the product label carefully before use. **Material Safety Data Sheets** are available by phoning **1800 077 744**.

***Please Note:-** The information given in this data sheet is based on our current knowledge of the product when properly stored, handled and applied. We cannot guarantee that the product will be suitable, effective or safe when used for any purpose other than its stated uses.*

*To the extent that it is lawful, we exclude warranties implied by law and limit our liability to the cost of replacing the product. We accept no responsibility for loss or injury caused by improper use, inadequate preparation, inexperienced or negligent application, or ordinary wear and tear.*

*Service or advice given by our staff should not amount to responsibility for the project - since the owner, or their contractor (and not River Sands), is responsible for procedures relating to the application of the product.*



**Concrete Colour Systems**  
**A Division of River Sands Pty Ltd**  
683 Beenleigh Redland Bay Rd,  
Carbrook Qld 4130  
Ph: 07 3287 6444 Fax: 07 3287 6445  
Toll Free Helpline: 1800 077 744  
[www.concretecoloursystems.com.au](http://www.concretecoloursystems.com.au)