

DESCRIPTION

CCS Solvent is a clear blend of liquid hydrocarbons formulated as a dilutant or extender in acrylic and lacquer coatings.

RECOMMENDED USES

- diluting acrylic sealers.
- diluting lacquer coatings.
- cleaning sealer application equipment.
- treating previously sealed concrete surfaces in readiness for new sealer applications.

PACKAGING

CCS Solvent is available in 5litre and 20 litre drums.

DILUTION RATES

Please refer to individual CCS acrylic sealer product data sheets or labels for appropriate dilution rates.

APPLICATION METHOD

CCS Solvent should be added to CCS acrylic sealers, stirring the solution until it is well mixed.

It is only necessary to dilute the first coat of sealer being applied to the surface of the concrete. Under normal circumstances there is no need to dilute any subsequent coats of sealer.

REPAIRING SEALER BLUSHING

Due to the entrapment of moisture under the surface of recently applied sealer an effect known as 'Sealer Blushing' can occur. This is similar to the phenomenon when one breathes on glass to create a fogging effect.

CCS Solvent can be used to assist the entrapped moisture escape from underneath the sealer coating.

Application of solvent under these circumstances should be done by applying liberal amounts of the solvent to the affected areas.

Allow the solvent to react with the sealer for approximately 30 seconds and then work it into the surface using a light rubbing motion with a broom.

For best results, this procedure should be performed in the cooler parts of the day to enable the solvent to react on the coating prior to it evaporating.

Allow the coating to dry and assess if the problem has been rectified.

If the problem has not been rectified, strip the surface with CCS Enviro Stripper, removing all traces of the sealer prior to resealing.

STORAGE

Store in a banded area or in an approved flammable store away from direct heat.

For further information consult the **Material Safety Data Sheet** and read the product label carefully before use. **Material Safety Data Sheets** are available by phoning **1800 077 744**.

Please Note:- The information given in this data sheet is based on our current knowledge of the product when properly stored, handled and applied. We cannot guarantee that the product will be suitable, effective or safe when used for any purpose other than its stated uses.

To the extent that it is lawful, we exclude warranties implied by law and limit our liability to the cost of replacing the product. We accept no responsibility for loss or injury caused by improper use, inadequate preparation, inexperienced or negligent application, or ordinary wear and tear.

Service or advice given by our staff should not amount to responsibility for the project - since the owner, or their contractor (and not River Sands), is responsible for procedures relating to the application of the product.