

CCS WB Stripper

DESCRIPTION

CCS WB Stripper is a blend of alkaline salts and water miscible solvents to remove even the most stubborn alkali sealers and polishes.

CCS WB Stripper has been formulated to remove conventional or metal cross linked floor polishes and sealers and it should be used prior to reapplying the CCS Sheen polish system.

CCS WB Stripper is suitable for removing water based sealers and polishes from concrete, vinyl, natural stone and tiles.

RECOMMENDED SURFACES

CCS WB Stripper is suitable for:-

- Concrete
- Vinyl
- Natural Stone
- Ceramic Tiles.

PACKAGING

CCS WB Stripper is available in a 20 litre drum.

DILUTION RATES

Application	CCS WB Stripper	Water
General Purpose Stripping	1 Litre	9 litres Warm Water
Heavily Polished Areas	3 litres	7 litres Hot Water

APPLICATION

1. Dilute CCS WB Stripper (as per the table above) in a bucket and apply with a mop or scrubbing machine. (If using an auto scrubbing machine, use a black scrubbing pad then remove the product and the stripped sealer with a conventional mop.)

2. Once the stripping process has been completed, the floor should be rinsed thoroughly and all residues removed. Once clean and dry, application of CCS Sheen can commence.
3. For problem areas a higher concentration of CCS WB Stripper may be required. To assist with neutralisation, add one cup of vinegar to 10 litres of water in the rinsing water.

STORAGE

Store CCS WB Stripper in a cool dry place away from Class 8 acids. The container should be sealed tightly whilst in storage. Always store away from food.

For further information consult the **Material Safety Data Sheet** and read the product label carefully before use. **Material Safety Data Sheets** are available by phoning **1800 077 744**.

Please Note:- The information given in this data sheet is based on our current knowledge of the product when properly stored, handled and applied. We cannot guarantee that the product will be suitable, effective or safe when used for any purpose other than its stated uses.

To the extent that it is lawful, we exclude warranties implied by law and limit our liability to the cost of replacing the product. We accept no responsibility for loss or injury caused by improper use, inadequate preparation, inexperienced or negligent application, or ordinary wear and tear.

Service or advice given by our staff should not amount to responsibility for the project - since the owner, or their contractor (and not River Sands), is responsible for procedures relating to the application of the product.