



Material Safety Data Sheet

CCS Petrol Resistant Sealer

Page 1 of 6

Issue Date: 29/10/08

Hazardous according to the criteria set by NOHSC

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

CONCRETE COLOUR SYSTEMS

A Division of River Sands Pty Ltd

ACN 009 919 215

ABN 41 009 919 215

683 Beenleigh Redland Bay Rd

CARBROOK QLD 4129

Tel: +61 7 3287 6444

Fax: +61 7 3287 6445

Emergency Advice All Hours:

Australia Wide: 131 126

Product Name: CCS Petrol Resistant Sealer

Use: Concrete and masonry coating.

UN Number: 1866

Proper Shipping Name: RESIN SOLUTION

Dangerous Goods Class: 3

Packing Group: III

Hazchem Code: 3[Y]

Poison Schedule: 5

2. COMPOSITION / INFORMATION ON INGREDIENTS

Chemical Name	Proportion	CAS Number
<i>Solvent naphtha, petroleum, light aromatic</i>	>60%	64742-95-6
<i>2-Propenoic acid, 2-methyl-, methyl ester, polymer with 2-ethylhexyl 2-propenoate</i>	10 -< 30%	25265-15-0

This material is listed on the Australian Inventory of Chemical Substances (AICS).

3. HAZARD IDENTIFICATION

Hazardous according to the criteria set by NOHSC, HAZARDOUS SUBSTANCE

Classified as Dangerous Goods by the criteria of the Australian Dangerous Goods Code (ADG Code) for Transport by Road and Rail; DANGEROUS GOODS.

Hazard Category: Class C – flammable liquid according to AS 1940

Hazard Classification: Xn Harmful

Risk Phrases

R10 Flammable

R20/21 Harmful by inhalation and in contact with skin

R38 Irritating to skin

R65 Harmful, May cause lung damage if swallowed

R66 Repeated exposure may cause skin dryness or cracking

R67 Vapours may cause drowsiness and dizziness

Safety Phrases

S2 Keep out of reach of children

S23 do not breathe in fumes

S24 Avoid skin contact



Material Safety Data Sheet

CCS Petrol Resistant Sealer

Page 2 of 6

Issue Date: 29/10/08

Hazardous according to the criteria set by NOHSC

S25 Avoid contact with eyes

3. HAZARD IDENTIFICATION (continued)

ACUTE HEALTH EFFECTS

Swallowed: May be harmful to mouth, throat and stomach with effects including irritation to the tongue and lips and pains in the stomach. There is some probability that this product could be aspirated into the lungs and hence, if vomiting occurs, this may lead to chemical pneumonitis.

Eye: May cause irritation to the eyes, with effects including tearing, pain, stinging and blurred vision

Skin: Harmful by skin contact, Will cause irritation to the skin, with effects including redness, itchiness, and drying/ defatting

Inhaled: Harmful if inhaled.

May cause irritation to the nose, throat and respiratory system. Effects include: Dizziness, headache, staggering gait, nausea and if the concentration of vapours is high enough, unconsciousness.

Chronic:

Prolonged or repeated skin contact may lead to dermatitis.

Prolonged exposure may lead to kidney and liver damage. Permanent central nervous system and blood changes occur due to high solvent exposure over time.

4. FIRST AID MEASURES

Swallowed: If swallowed, **DO NOT induce vomiting**. If victim is conscious, give glass of water to drink. Seek urgent medical attention.

Eye: If material is splashed into eyes, flush with plenty of water for at least 15 minutes, ensuring eye lids are held open. Immediately, seek medical attention.

Skin: If material is splashed onto the skin, remove any contaminated clothing and wash skin thoroughly with water and soap if available. Seek medical attention if irritation persists.

Inhaled: Remove victim to fresh air. Apply resuscitation if victim is not breathing - Administer oxygen if breathing is difficult. Seek medical attention.

First Aid Facilities: Eye wash fountain, safety shower and normal wash room facilities.

Advice to Doctor:

Treat symptomatically as for exposure to aromatic hydrocarbon solvents. Aspiration can result in pulmonary oedema. Gastric lavage should only be undertaken after endotracheal intubation.

5. FIRE-FIGHTING MEASURES

Fire/Explosion Hazard

EXTINGUISHING MEDIA: Use dry chemical, carbon dioxide or foam.

SPECIAL FIRE FIGHTING PROCEDURES: Self-contained breathing apparatus (SCBA) required for fire-fighting personnel. If possible to do so safely, shut off fuel to fire. Use water spray to cool fire-exposed surfaces and to protect personnel. Avoid spreading burning liquid with water used for cooling fire exposed containers when using water spray boil-over may occur when the product temperature reaches the boiling point of water.

UNUSUAL FIRE AND EXPLOSION HAZARDS: Vapours from this product may travel or be moved by air currents and be ignited by pilot lights, other flames, smoking, sparks, heaters, electrical equipment, static discharge or other ignition sources at locations distant from the point of handling.



Material Safety Data Sheet

CCS Petrol Resistant Sealer

Page 3 of 6

Issue Date: 29/10/08

Hazardous according to the criteria set by NOHSC

FLAMMABILITY: Flammable liquid. Avoid all sources of ignition, heat and naked flames. Vapours may travel a considerable distance to source of ignition and ignite.

6. ACCIDENTAL RELEASE MEASURES

EMERGENCY ACTION:

Keep unnecessary people away; Isolate hazard area and deny entry. Stay upwind; Keep out of low areas.

SPILL OR LEAK PROCEDURE:

Extinguish or remove all sources of ignition. Clear area of all unprotected personnel. Wear appropriate protection equipment. Do not contaminate streams, rivers or watercourses. Do not flush drains or sewers. Inform local authority if liquid enters drains, sewers, streams etc. Shut off sources of leak if safe to do so. Dike and contain spill with sand or earth.

SMALL SPILLS:

Absorb the liquid with sand, earth or other absorbent. Place used absorbent in suitable, sealable, labeled containers. Keep away from heat, naked flame or sparks.

LARGE SPILLS:

Notify Emergency Services (Police or Fire Brigade). Tell them exact location, nature, hazards, quantities, type of vehicle and any other information that would be helpful. Contain spill. Trained personnel should wear Personal Protective equipment as highlighted in this MSDS. Take up liquid with vacuum truck or absorb with sand, earth or other absorbent. Place used absorbent in suitable, sealable, labeled containers. Keep away from heat, naked flame or sparks. **Consult an expert regarding disposal of this product.**

7. HANDLING AND STORAGE

Precautions for safe handling

Avoid skin and eye contact and breathing in vapour, mists and aerosols.

Containers that have been emptied can contain hazardous product residues. Avoid all body contact. Wash with soap and water before eating, drinking, smoking, applying cosmetics, or using toilet facilities. Launder contaminated clothing before reuse. Contaminated leather articles including shoes cannot be decontaminated and should be destroyed to prevent reuse.

Conditions for safe storage

Store in a cool place and out of direct sunlight.

Store away from sources of heat or ignition, strong alkalis, acids, combustibles and oxidizing agents. All equipment must be earthed. Take precautionary measures against static electricity.

Store in original packages as approved by manufacturer. Check all fittings, valves, reticulation (piping) and any ancillary equipment for leaks.

A supplied air respirator or a Self-Contained Breathing Apparatus (SCBA) for emergencies should be available and checked regularly. For further information please refer to the Engineering Controls of this MSDS.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure Standards

No exposure standards are available for this product, or for the components of the product:

Engineering Controls

Where mists or vapours are generated exhaust ventilation should be provided to maintain airborne concentration levels as low as reasonably practicable.

Provide explosion proof ventilation system. Maintain adequate ventilation. Performance of ventilation system should be regularly monitored. If air contaminant levels exceed the exposure limit, respiratory protection is required.

Personal Protection Equipment

CLOTHING: Long sleeved overalls and safety boots.

GLOVES: PVC or rubber.

EYES: Safety glasses or chemical goggles.

RESPIRATORY PROTECTION: If engineering controls are not effective in controlling airborne exposure then an approved respirator with a replaceable organic vapour filter should be used. Reference should be made to Australian Standards



Material Safety Data Sheet

CCS Petrol Resistant Sealer

Page 4 of 6

Issue Date: 29/10/08

Hazardous according to the criteria set by NOHSC

AS/NZS 1715, Selection, Use and Maintenance of Respiratory Protective Devices; and AS/NZS 1716, Respiratory Protective Devices, in order to make any necessary changes for individual circumstances.

CONTAMINATION:

If contamination occurs, change clothing and discard internally contaminated gloves and footwear. Launder contaminated clothing before reuse. Observe good personal hygiene.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance:	Black viscous Liquid
Boiling Point:	138 - 145°C
Vapour Pressure:	7.5 kPa @ 38°C *
Specific Gravity:	0.94 – 1.05 (H ₂ O = 1)
Flash Point:	24°C (PMCC)
Flammability Limits:	LEL: 1.0 % * UEL: 7.5 % *
Solubility in Water:	Insoluble
Evaporation Rate:	2.7 (Butyl acetate = 1) *
Vapour Density:	3.38 (Air =1) *
Odour:	Aromatic hydrocarbon
Form:	Liquid
Other Information:	* for Petroleum aromatic hydrocarbon
Percent Volatiles:	40 %

10. STABILITY AND REACTIVITY

STABILITY: Stable under normal conditions of use.

HAZARDOUS DECOMPOSITION PRODUCTS: Emits oxides of carbon when heated to decomposition.

HAZARDOUS POLYMERIZATION: Will not occur.

INCOMPATIBILITIES: Halogens, molten sulfur, strong oxidising agents.

CONDITIONS TO AVOID: Heat, flames, ignition sources and incompatibles.

11. TOXICOLOGICAL INFORMATION

Acute Data Not established for this product

Swallowed: Harmful to mouth, throat and stomach. There is some probability that this product could be aspirated into the lungs and hence, if vomiting occurs, this may lead to chemical pneumonitis which can be fatal.

Eye: May cause irritation to the eyes, with effects including tearing, pain, stinging and blurred vision.

Skin: Harmful by skin contact. Effects including redness, itchiness, drying and defatting

Inhalation: Harmful by inhalation may cause lung damage, central nervous system depression, May cause irritation to the nose, throat and respiratory system with effects including Dizziness, headache staggering gait, nausea and if the concentration of vapours is high enough, and unconsciousness.

Chronic: Prolonged or repeated skin contact may lead to dermatitis.

Prolonged exposure may lead to kidney and liver damage. Permanent central nervous system and blood changes occur due to high solvent exposure over time.



Material Safety Data Sheet

CCS Petrol Resistant Sealer

Page 5 of 6

Issue Date: 29/10/08

Hazardous according to the criteria set by NOHSC

Carcinogen: Product contains no known substances indicated to have carcinogenetic effects.

12. ECOLOGICAL INFORMATION

No environmental impact information is available for this product, however for:

13. DISPOSAL CONSIDERATIONS

Refer to appropriate authority in your State. Dispose of material through a licensed waste contractor. Advise flammable nature. Normally suitable for disposal by approved waste disposal agent.

14. TRANSPORT INFORMATION

UN Number: 1866

Proper Shipping Name: RESIN SOLUTION

Dangerous Goods Class: 3

Packing Group: III

Hazchem Code: 3[Y]

Classified as a CLASS 3 (FLAMMABLE LIQUID) Dangerous Goods according to the Australian Code for the Transport of Dangerous Goods by Road and Rail, 6th Edition

Dangerous goods of Class 3 (Flammable Liquid) are incompatible in a placard load with any of the following:

- Class 1, Explosives
- Class 2.1, Flammable Gases, if both the Class 3 and Class 2.1 dangerous goods are in bulk
- Class 2.3, Toxic Gases
- Class 4.2, spontaneously combustible Substances
- Class 5.1, Oxidising Agents
- Class 5.2, Organic Peroxides
- Class 6, Toxic Substances if the Class 3 dangerous goods are nitromethane
- Class 7, Radioactive Substances.

Emergency information (Transport):

Dangerous Goods - Initial Emergency Response Guide (SAA/SNZ HB76:1997)

For LIQUIDS - FLAMMABLE, Guide No: 15

15. REGULATORY INFORMATION

Poison Schedule: S6

This material is a Scheduled (S6) Poison and must be stored, handled and used in accordance with the relevant regulations.

Hazardous according to the criteria set by NOHSC

Classified as Dangerous Goods by the criteria of the Australian Dangerous Goods Code (ADG Code) for Transport by Road and Rail; DANGEROUS GOODS.

Hazard Category: Class C – flammable liquid according to AS 1940

Hazard Classification: Xn Harmful

Risk Phrases

R10 Flammable

R20/21 Harmful by inhalation and in contact with skin

R38 Irritating to skin

R65 Harmful, May cause lung damage if swallowed

R66 Repeated exposure may cause skin dryness or cracking



Material Safety Data Sheet

CCS Petrol Resistant Sealer

Page 6 of 6

Issue Date: 29/10/08

Hazardous according to the criteria set by NOHSC

R67 Vapours may cause drowsiness and dizziness

Safety Phrases

- S2** Keep out of reach of children
S23 do not breathe in fumes
S24 Avoid skin contact
S25 Avoid contact with eyes

16. OTHER INFORMATION

Sources for data: Suppliers MSDS for component ingredients
National Code of Practice for the Preparation of Material Safety Data Sheets 2nd Ed
[NOHSC: 2011(2003)]
Approved Criteria for Classifying Hazardous Substances [NOHSC: 1008(1999)]

The customer is advised to consult the product Technical Data Sheets for further information including advice on suitable equipment.

Information used in the compilation of this MSDS obtained from investigations conducted at outside laboratories.

REASONS FOR UPDATE:

1. Product release
2. Revision Date 29/10/2008

MSDS's are updated frequently. Please ensure that you have a current copy.

Contact Point

Emergency Advice All Hours:

Australia Wide: 131 126

River Sands Pty Ltd

Tel: +61 7 3287 6444

Fax: +61 7 3287 6445

Contact: Paul Moorfoot – General Manager

Disclaimer

This Material Safety Data Sheet should be used in conjunction with the Technical Data Sheet. It does not replace them. The information given is based on our knowledge of the health and safety data of this product, at the time of publication. It is given in good faith. The attention of the user is drawn to the possible risks incurred by using the product for any purpose other than that for which it was intended. If clarification or further information is needed to enable appropriate risk assessment, the user should contact River Sands Pty Ltd. Our responsibility for products sold is subject to our standard terms and conditions sent to customers. No liability whatsoever can be accepted with regard to the handling, processing or use of the product concerned which, in all cases, shall be in accordance with the appropriate regulations and / or legislation. **END OF DOCUMENT**